

RECORD OF SURVEY

NO. 34 - 37

LS 3670
TIS
R26E R27E
S36 S31
S1 S6
T2S
1979

319-81.02
140.03 LT.
MARKED 31+06.34
140 LT.
PER 1000 SCALE R/W
MAP IX-MNO-23-G
N 2120148.368
DATED OCT. 31, 1955
E 6980821.232

SECTION 31

T. 1 S., R. 27 E.,

M.D.M.


"TWP. COR. FOUND
NOTCHED 4" x 4" x 3"
HEWN PINE STAKE IN
MOUND OF STONES."
F.B. MNO 23-F 680-B/18
NOVEMBER 1915
"MOUND OF ROCKS WITH
STICK IN CENTER, 2
BEARING TREES."
F.B. MNO 3058/26
SEPTEMBER 1967
COORDINATE VALUES
REFLECT TIE TO THIS
DESCRIPTION IN 1978.

N 2119748.637
E 6980481.862

FD. 2.5 INCH O.D.I.P.
WITH 3 INCH DIA. BRASS
CAP, MARKED AS SHOWN,
FIRMLY SET, UP 0.7' IN A
MOUND OF STONES 3 FT. DIA.
TWO NEARBY TREES WITHOUT
VISIBLE SCARS WITH U.S.F.S.
1952 TAGS.

SECTION 3

T. 2 S., R. 27 E., M.D.M.



0 50 100
SCALE 1 INCH = 100 FEET

GEODETIC AZIMUTH = GRID AZIMUTH + CONVERGENCE ANGLE
CONVERGENCE ANGLE AT 310+76.82 175.56 LT. = 0° 53' 23"

TO OBTAIN A GROUND DISTANCE, DIVIDE THE GRID
DISTANCE BY THE GRID FACTOR.
COMBINED GRID FACTOR = 0.99956071

LEGEND

- ① T-BAR AND CAP
- ⊙ CALIF. DIV. OF HIGHWAYS BRASS CAP
- ▼ CALTRANS ALUMINUM CAP ON 3/4 INCH REBAR
- ◆ LAND NET CORNER AS NOTED
- TYPE "C" 6 INCH SQ. CONCRETE R/W MONUMENT
- RIGHT-OF-WAY LINES, STATE ROUTE MNO 395

R/W CENTERLINE ALIGNMENT DATA

301+0.80 E.C.
N 211923.915
E 6982403.774

306+37.13 B.C.
N 2119402.225
E 6981957.046

RADIUS = 4,997.80'
DELTA = 11° 46' 17"
LENGTH = 1,026.80'

316+63.93 E.C.
N 2120030.569
E 6981147.237

329+00.00 P.O.T.
N 2120884.457
E 6980253.512

PM 39.4
300+06.27
244.31 LT.
N 2118866.584
E 6982349.831
EL = 7865.46

300+07.15
194.39 LT.
MARKED 300+6.30
195.54 LT.
N 2118907.807
E 6982378.004

299+77.19
164.92 RT.
MARKED 299+86.31
165 RT.
N 211982.247
E 6982611.805

R/W AT
164.93 RT 299+77.19 POC
N 211982.248
E 6982611.808

"1/4 COR. FOUND SQUARED STAKE
2 1/2" x 3" & BLAZED TREE."
F.B. MNO 23-F 680-B/18, NOVEMBER 1915
"FD. ORIGINAL STAKE REBUILT WITH
ROCKS." F.B. MNO 23-G, 4/78 MARCH 1930.
"MOUND OF ROCKS W/STICK IN CENTER,
2 BEARING TREES." F.B. MNO 3058/26
FD. MOUND OF STONES 2 FT. DIA. SET
3.25 INCH CALIF. D.O.T. CAP, MARKED AS
SHOWN, UP 0.1 FT. IN MOUND OF STONES
AND ASPHALT. A 1.4 FT. DIA. BLAZED
PINE WITH A TAG ON W'ly FACE BEARS
S 65° E 33.8 FT. A 3.5 FT. DIA. PINE
WITHOUT VISIBLE MARKINGS WITH 1970
AND 1948 U.S.F.S. TAGS AND TAG ON
S'ly FACE BEARS S 66° W 76.3 FT.

TIS
R 27 E
S 31
S 6
T 2 S
1966

31

N 2119690.015
E 6983146.294

3